

# Alu ThermoWood

## & PROFILES

**FIBROTECH**  
 BY TREE TOPS


Alu ThermoWood Panel - Oiled



Alu ThermoWood Panel - Natural



Alu ThermoWood Panel - Grey



Alu ThermoWood Panel - Black



Alu Wood Screw - Black

Visualization with Al



Start/End Profile




Top/Side Profile



Cover Profile 200 mm



Cover Profile 250 mm



Outside Profile



Inside Profile



Bottom/Divider Profile



Door/Window Sill Profile



Coverage Profile



Insect Mesh Profile

### ALU THERMOWOOD PANELS

Give your façade an attractive and natural wood appearance without the need for ongoing maintenance. The wood slats are securely mounted on a powder-coated aluminum backing plate. The aluminum construction contributes to a stable and uniform façade.

FibroTech Alu ThermoWood Panels are developed for Nordic outdoor conditions and

require only minimal maintenance compared to traditional timber cladding.

The surface does not require oil treatment – the wood can remain untreated and will gradually develop a beautiful silver-grey patina over time. If a silver-grey appearance is not desired, the surface can be oiled 1–2 times per year, depending on environmental and weather exposure.

The product properties are based on testing and material characteristics and may vary depending on application and installation conditions.

FibroTech Alu ThermoWood Panels are available in 4 colors: Black, Grey, Natural and Oiled.

The panels can advantageously be installed using our accessories program and screws.

| DB nr.  | Produkt                      | Farve                 | Dimensioner          | m <sup>2</sup><br>pr. panel | Antal<br>pr. palle | Vægt<br>pr. stk. |
|---------|------------------------------|-----------------------|----------------------|-----------------------------|--------------------|------------------|
| 2575558 | Alu ThermoWood Panel         | Oiled                 | 25 x 194,5 x 2440 mm | 0,47 m <sup>2</sup>         | 80 stk.            | 2,75 kg          |
| 2575562 | Alu ThermoWood Panel         | Natural               | 25 x 194,5 x 2440 mm | 0,47 m <sup>2</sup>         | 80 stk.            | 2,75 kg          |
| 2575563 | Alu ThermoWood Panel         | Grey                  | 25 x 194,5 x 2440 mm | 0,47 m <sup>2</sup>         | 80 stk.            | 2,75 kg          |
| 2575564 | Alu ThermoWood Panel         | Black                 | 25 x 194,5 x 2440 mm | 0,47 m <sup>2</sup>         | 80 stk.            | 2,75 kg          |
| 2624660 | Bottom and Divider Profile   | Black                 | 111 x 2440 mm        |                             | 100 stk.           | 1,75 kg          |
| 2624666 | Coverage Profile             | Black                 | 115,5 x 2440 mm      |                             | 100 stk.           | 1,75 kg          |
| 2624669 | Inside Corner Profile        | Black                 | 114,7 x 2440 mm      |                             | 100 stk.           | 1,75 kg          |
| 2624670 | Outside Corner Profile       | Black                 | 100 x 2440 mm        |                             | 100 stk.           | 1,75 kg          |
| 2624671 | Insect Mesh Profile          | Black                 | 50 x 2440 mm         |                             | 100 stk.           | 1,75 kg          |
| 2624673 | Cover Profile 200 mm         | Black                 | 200 x 2440 mm        |                             | 100 stk.           | 1,75 kg          |
| 2624674 | Cover Profile 250 mm         | Black                 | 250 x 2440 mm        |                             | 100 stk.           | 1,75 kg          |
| 2624675 | Start and End Profile        | Black                 | 122 x 2440 mm        |                             | 100 stk.           | 1,75 kg          |
| 2624677 | Door and Window Sill Profile | Black                 | 138 x 2440 mm        |                             | 100 stk.           | 1,75 kg          |
| 2624678 | Top and Side Profile         | Black                 | 122 x 2440 mm        |                             | 100 stk.           | 1,75 kg          |
| 2563345 | Alu Wood Screw               | Futura Noir 900 Sable | 4,8 x 35 mm TX20     |                             | 100 stk.           |                  |



Certifications, fire classifications, and environmental documentation depend on the product variant and application. Relevant certificates and declarations of conformity are available upon request. No rights may be derived from this document. We reserve the right to make changes and accept no responsibility for typographical or printing errors.

Scan for the latest version: <https://fibrotech.com/en/product-information/>



The mark of  
responsible forestry

Vers: TT 001  
02.07.2026